

MileMaster EP GL-4 Gear Lubes

DESCRIPTION:

Milemaster EP GL-4 Gear Lubes are formulated with naturally high VI refined base stocks. They also contain state of the art additive systems to assure excellent anti-weld, anti-scuff, and anti-wear properties.

QUALITIES:

MileMaster EP GL-4 Gear Lubes have the following qualities to make them excellent products for GL-4 applications:

- Excellent extreme pressure (EP) and anti-weld performance protection where equipment manufacturers recommend a GL-4 product.
- Provides excellent rust protection.
- Excellent viscometrics properties throughout their useful life and will not experience rapid viscosity loss through shear.

APPLICATIONS:

MileMaster EP GL-4 Gear Lubes are recommended for performance requirements for API GL-4 and MT-1. They are also recommended for manual transmissions, axles, and other gear boxes where these API and SAE grades are required.

TYPICAL PROPERTIES:

	SAE 85W90	SAE 140
Material Code	663723008	663776008
Gravity, ASTM D 4052, API	27.4	23.3
Pounds per gallon	7.6	7.6
Flash Point, ASTM D92, F	430	470
Viscosities		
At 40 C cST	240	600
At 100 C, cST	16.0	27
Viscosity Index, ASTM D 2270	95	93
Pour Point, ASTM D-97 F	-20	-5
Color	Dark Amber	Dark Amber