

# SERVICE PRO<sup>®</sup>

## Premium Lubricants

### SERVICE PRO<sup>®</sup> PREMIUM FULL SYNTHETIC MOTOR OILS

Manufactured with highly refined virgin base oils and licensed additive systems

**DESCRIPTION:** SERVICE PRO<sup>®</sup> Premium Full Synthetic GF-5 Motor Oils are top tier, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

SERVICE PRO Full Synthetic GF-5 Motor Oils meet or exceed the requirements of GM 6094M (0W-20, 5W-20, 5W-30, 10W-30) and Ford WSS-M2C945-A (SAE 5W-20) and WSS-M2C946-A (SAE 5W-30), Chrysler MS-6395 (SAE 0W-20, SAE 5W-30). Meets Toyota Specifications, and Honda Service Fill Specifications (SAE 0W-20, SAE 5W-20, SAE 5W-30 and SAE 10W-30). All grades meet or exceed API Service Category SN, SM, SL, SJ and comply with ILSAC GF-5 requirements.

**PERFORMANCE  
BENEFITS:**

- Our highest level of protection for thermal and oxidation stability
- Formulated for extreme driving conditions
- Outperforms conventional and synthetic blends
- Outstanding low and high temperature performance
- ILSAC GF-5 Resource Conserving

TYPICAL PROPERTIES:	SAE Grade	0W-20	5W-20	5W-30	10W-30
API Gravity @ 60°F		34.9	32.6	33.7	33
Sp. Gr. @ 60°F		0.8504	0.8478	0.849	0.852
Flash, COC, °F		405	405	405	405
Pour Pt., °F		-48	-40	-40	-35
Viscosity,					
cSt @ 40°C		45	43.3	57.3	62.8
cSt @ 100°C		8.5	7.8	10	10.5
Viscosity Index		170	150	162	156
Zinc, Wt. %		0.0856	0.0836	0.0839	0.082
Phosphorus, Wt. %		0.0767	0.0768	0.0763	0.0746
API Performance		SN	SN	SN	SN



Updated: 2/11

SPWNFSMO