

# SERVICE PRO®

## Premium Lubricants

## SERVICE PRO® PREMIUM SYNTHETIC BLEND MOTOR OILS

Manufactured with highly refined virgin base oils and licensed additive systems

**DESCRIPTION:** SERVICE PRO® Premium Synthetic Blend Motor Oils are superior-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. A unique blend of synthetic and high viscosity index mineral oils combine with a carefully selected additive package to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

SERVICE PRO® Premium Synthetic Blend Motor Oils meet or exceed the requirements of MIL-1-46152E, Ford WSSM2C153-H and WSS-M2C930-A (SAE 5W-20) and WSS-M2C929-A (SAE 5W-30) Meets DaimlerChrysler DC MS10797 (SAE5W-20), DC MS10796 (SAE 5W-30), DC MS10798 (SAE 10W-30) specifications and engine test requirements of DC MS6395.

Meets API Service Category SM, SL and SJ, complies with ILSAC GF-4 (5W20, 5W30 & 10W30) requirements. Meets Honda Service Fill Specifications, GM 6094M Specification (SAE 5W-20, SAE 5W30 and SAE 10W30) and Toyota.

**PERFORMANCE  
BENEFITS:**

- Provides outstanding thermal and oxidation stability
- Helps protect emissions system
- Minimized rust and corrosion
- Outstanding low temperature pour point
- ILSAC GF-4 Energy Conserving

TYPICAL PROPERTIES:	SAE Grade	5W20	5W30	10W30
Viscosity				
@40 Deg. C, cSt		47.5	60.9	66.4
@100 Deg. C, cSt		8.2	10.4	10.5
Viscosity Index		146	160	146
API Gravity		32.5	33.6	31.1
Sp. Gravity		0.8618	0.8560	0.8692
Pounds per gallon		7.19	7.14	7.24
Flash, COC, °F		405	405	405
Pour Pt., °F		-40	-40	-35
API Performance		SM	SM	SM

